



MODELO	Torque Nominal (Nm)	Torque Máximo (Nm)	Furo Máx. (d)	Rpm Máx	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	Ângulo Torção	Peso (Kg)
BP - 25 L	45	90	32	5000	95	74	66	80	25	5°	3
BP - 35 L	90	180	45	4000	127	96	86	110	35	4°	4
BP - 50 L	340	680	60	3600	166	127	110	150	50	6°	9
BP - 70 L	940	1880	90	3250	222	169	150	205	70	9°	23
BP - 90 L	1700	3400	100	2000	302	218	190	250	80	6°	45
BP - 105 L	2500	5000	125	2000	330	235	202	290	100	8°	61
BP - 140/100 L	6800	13600	170	1400	402	287	270	320	100	9°	132
BP - 140/140 L	6800	13600	170	1400	402	287	270	380	130	9°	132
BP - 200/90 L	20150	40300	240	1000	550	436	380	385	100	11°	390
BP - 200/140 L	20150	40300	240	1000	550	436	380	445	130	11°	390
BP - 200/200 L	20150	40300	240	1000	550	436	380	545	180	11°	390
BP - 300/150 L	68900	137800	325	720	730	535	490	555	160	10°	880
BP - 300/200 L	68900	137800	325	720	730	535	490	635	200	10°	880
BP - 300/250 L	68900	137800	325	720	730	535	490	785	275	10°	880
BP - 300/300 L	68900	137800	325	720	730	535	490	785	275	10°	880