



MODELO	Torque Nominal (Nm)	Torque Máximo (Nm)	Furo Máx. (d)	Rpm Máx.	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	Ângulo Torção	Peso (Kg)
BP - 25	45	90	24	5000	95	74	36	80	25	30	5°	1,5
BP - 35	90	180	32	4000	127	96	49	110	35	40	4°	2,5
BP - 50	340	680	46	3600	166	127	70	150	50	50	6°	5,5
BP - 70	940	1880	65	3250	222	169	100	205	70	65	9°	13,5
BP - 90	1700	3400	85	2000	302	218	116	250	80	90	6°	28
BP - 105	2500	5000	100	2000	330	235	138	290	100	90	8°	42
BP - 140/100	6800	13600	100	1400	402	287	150	320	100	120	9°	67
BP - 140/140	6800	13600	140	1400	402	287	195	380	130	120	9°	95
BP - 200/90	20150	40300	90	1000	550	436	150	385	100	185	11°	190
BP - 200/140	20150	40300	140	1000	550	436	195	445	130	185	11°	230
BP - 200/200	20150	40300	200	1000	550	436	274	545	180	185	11°	250
BP - 300/150	68900	137800	150	720	730	535	225	555	160	235	10°	370
BP - 300/200	68900	137800	200	720	730	535	290	635	200	235	10°	450
BP - 300/250	68900	137800	250	720	730	535	350	785	275	235	10°	640
BP - 300/300	68900	137800	300	720	730	535	390	785	275	235	10°	695